

Luminaire

AESTETICA 32 LED 24W SE 1H

B16224



AESTETICA 32 LED 24W SE 1H

	B16224
Mounting method	Surface mounting/recessed mounting
Function	Escape route lighting
Suitable for standby switching	Yes
Suitable for continuous circuit	No
Emergency power supply system	Peripheral (individual battery)
Battery technology	NiMH
With heating element for battery	No
Lamp type	LED not exchangeable
With light source	Yes
Suitable for number of light sources	32
Lamp holder	None
Number of lighting heads	1
Housing material	Plastic
RAL-number housing	9003
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	207 - 4000 V
Light distributor	Diffuser lens/optic/panel
Degree of protection (IP)	IP40
Impact strength	IK05
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	0 - 1 °C
Luminous flux in emergency mode	225 lm
Rated luminous flux according to IEC 62722-2- 1	0 lm

AESTETICA 32 LED 24W SE 1H

	B16224
Max. system power	0.8 W
Luminous flux in standby mode	0 lm
Colour temperature	4000 - 40 K
Recognition distance	16 m
Nominal operation time	1 - 0 h
Width	102 mm
Height/depth	34.6 mm
Length	292 mm
Built-in width	94 mm
Built-in length	279 mm

Brand	BEGHELLI
Art. N°	B16224
Sales unit	pc
EAN PCE	8002219602640
EAN QTY PCE	1
EAN C01	8002219602640
EAN QTY C01	12
Intrastat code	85393110