

Luminaire

AESTETICA 16 LED 8W SE/SA3H

B16225



AESTETICA 16 LED 8W SE/SA 3H

	B16225
Mounting method	Wall surface mounting/ceiling surface mounting
Function	Escape route lighting
Type of indicator	Single-sided
Suitable for standby switching	Yes
Suitable for continuous circuit	Yes
Emergency function monitoring system	Automatic self test
Emergency power supply system	Peripheral (individual battery)
Battery technology	NiMH
Lamp type	LED not exchangeable
With light source	Yes
Suitable for number of light sources	16
Lamp holder	None
Number of lighting heads	1
Housing material	Plastic
RAL-number housing	9003
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	230 - 230 V
Type of control gear	LED operating device current-controlled
Light distributor	Diffuser lens/optic/panel
Degree of protection (IP)	IP40
Impact strength	IK05
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	0 - 40 °C

AESTETICA 16 LED 8W SE/SA3H

	B16225
Luminous flux in emergency mode	105 lm
Rated luminous flux according to IEC 62722-2- 1	70 - 105 lm
Max. system power	1 W
Power consumption in emergency mode	1 W
Luminous flux in standby mode	105 lm
Colour temperature	4000 - 4000 K
Recognition distance	16 m
Nominal operation time	3 - 3 h
Width	102 mm
Height/depth	34.6 mm
Length	292 mm
Built-in width	94 mm
Built-in length	279 mm

Brand	BEGHELLI
Art. N°	B16225
Sales unit	pc
EAN PCE	8002219609632
EAN QTY PCE	1
Intrastat code	85393110