

Luminaire

F65 LED 8w IP65 SE 1N

B19202N



F65 LED 11W IP65 SE 1/3 LF

	B19202N
Mounting method	Surface mounting/recessed mounting
Function	Escape route lighting
Emergency power supply system	Peripheral (individual battery)
Battery technology	Lithium-ion
Type of lithium-ion battery	Lithium iron phosphate (LiFePO4)
Lamp type	LED not exchangeable
With light source	Yes
Lamp holder	None
Housing material	Plastic
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	207 - 4000 V
Type of control gear	LED operating device current-controlled
Light distributor	Diffuser lens/optic/panel
Degree of protection (IP)	IP65
Impact strength	IK07
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	0 - 3 °C
Luminous flux in emergency mode	200 lm
Max. system power	11 W
Power consumption in emergency mode	2.6 W
Colour temperature	4000 - 40 K
Recognition distance	25 m
Nominal operation time	1 h

F65 LED 8w IP65 SE 1N

	B19202N
Width	354 mm
Height/depth	49 mm
Length	152 mm

Brand	BEGHELLI
Art. N°	B19202N
Sales unit	pc
EAN PCE	8002219878731
EAN QTY PCE	1
EAN C01	8002219878748
EAN QTY C01	6
Intrastat code	94051940