

Luminaire

F65 LED DEEP 11w AT OPT SA8LTO

B19219



F65 LED DEEP 24W CT SA LF

	B19219
Mounting method	Surface mounting/recessed mounting
Function	Escape route lighting
Emergency function monitoring system	Automatic self test
Emergency power supply system	Peripheral (individual battery)
Battery technology	Lithium-ion
Type of lithium-ion battery	Other
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Plastic
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	230 - 230 V
Light distributor	Reflector
Degree of protection (IP)	IP65
Impact strength	IK07
Rated ambient temperature according to IEC 62722-2-1	-40 - 50 °C
Luminous flux in emergency mode	130 lm
Rated luminous flux according to IEC 62722-2- 1	130 - 130 lm
Max. system power	11 W
Power consumption in emergency mode	7.5 W
Colour temperature	4000 - 4000 K
Nominal operation time	1 - 8 h
Width	152 mm
Height/depth	48.5 mm

F65 LED DEEP 11w AT OPT SA8LTO

	B19219
Length	354 mm
Type of wiring	Loop-through wiring included
Conductor cross section	2.5 mm ²
Connectable conductor cross section	2.5 - 2.5 mm ²

Brand	BEGHELLI
Art. N°	B19219
Sales unit	pc
EAN PCE	8002219733184
EAN QTY PCE	1
EAN C01	8002219833181
EAN QTY C01	5
Intrastat code	94051940