

Luminaire

F65LED 24W IP65 CT SA LF

B19294



F65LED 24W IP65 CT SA LF

	B19294
Mounting method	Surface mounting/recessed mounting
Function	Escape route lighting
With pictogram	Yes
Emergency function monitoring system	Automatic self test
Emergency power supply system	Peripheral (individual battery)
Battery technology	Lithium-ion
Type of lithium-ion battery	Lithium iron phosphate (LiFePO4)
Lamp type	LED not exchangeable
With light source	Yes
Lamp holder	None
Housing material	Plastic
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	230 - 230 V
Light distributor	Diffuser lens/optic/panel
Degree of protection (IP)	IP65
Impact strength	IK07
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	0 - 40 °C
Luminous flux in emergency mode	500 lm
Max. system power	24 W
Power consumption in emergency mode	4 W
Luminous flux in standby mode	250 lm
Colour temperature	4000 - 4000 K

F65LED 24W IP65 CT SA LF

	B19294
Recognition distance	25 m
Nominal operation time	1 - 8 h
Width	354 mm
Height/depth	49 mm
Length	152 mm

Brand	BEGHELLI
Art. N°	B19294
Sales unit	pc
EAN PCE	8002219730411;8002219830418
EAN QTY PCE	1
Intrastat code	85393110