

Luminaire

F65 LED 24GL IP65 AT OPT SA8LTO

B19296



F65LED 36WGL IP65 CT SA LF

	B19296
Mounting method	Wall surface mounting/ceiling surface mounting
Function	Escape route lighting
With pictogram	Yes
Emergency function monitoring system	Automatic self test
Emergency power supply system	Peripheral (individual battery)
Battery technology	Lithium-ion
Type of lithium-ion battery	Lithium iron phosphate (LiFePO4)
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Plastic
Housing colour	Blue
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	230 - 230 V
Degree of protection (IP)	IP65
Impact strength	IK07
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	0 - 40 °C
Luminous flux in emergency mode	1000 lm
Max. system power	36 W
Power consumption in emergency mode	4 W
Luminous flux in standby mode	250 lm
Colour temperature	4000 - 4000 K
Recognition distance	25 m
Nominal operation time	1 - 8 h

F65 LED 24GL IP65 AT OPT SA8LTO

	B19296
Width	354 mm
Height/depth	49 mm
Length	152 mm

Brand	BEGHELLI
Art. N°	B19296
Sales unit	pc
EAN PCE	8002219730435
EAN QTY PCE	1
EAN QTY C01	6
Intrastat code	94051940