

Luminaire

LUNGALARGALUCE EXTREME OPTICOM

B19370



LUNGALARGALUCE EX CT SE/SA LF

	B19370
Mounting method	Wall surface mounting/ceiling surface mounting
Function	Escape route lighting
Emergency function monitoring system	Automatic self test
Emergency power supply system	Peripheral (individual battery)
Battery technology	Lithium-ion
Type of lithium-ion battery	Lithium iron phosphate (LiFePO4)
Lamp type	LED not exchangeable
With light source	Yes
Lamp holder	None
Housing material	Aluminium
Housing colour	Grey
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	230 - 230 V
Type of control gear	LED operating device current-controlled
Light distributor	Focal lens
Degree of protection (IP)	IP65
Impact strength	IK09
Protection class according to IEC 61140	I
Rated ambient temperature according to IEC 62722-2-1	0 - -45 °C
Luminous flux in emergency mode	575 lm
Rated luminous flux according to IEC 62722-2- 1	575 - 575 lm
Max. system power	24 W
Power consumption in emergency mode	7.5 W
Colour temperature	4000 - 4000 K
Nominal operation time	1 - 8 h
Width	179 mm

LUNGALARGALUCE EXTREME OPTICOM

	B19370
Height/depth	57 mm
Length	183 mm
Built-in height/depth	57 mm
Built-in length	170 mm

Brand	BEGHELLI
Art. N°	B19370
Sales unit	pc
EAN PCE	8002219739575
EAN QTY PCE	1
EAN C01	8002219839572
EAN QTY C01	6
Intrastat code	94051940