

Luminaires

INFINITA RTI IP65 NOT PERMANENT CBL LTO XL

B19451



INFINITA RTI CT SE LF XL

	B19451
Mounting method	Surface mounting/recessed mounting
Function	Escape route lighting
Emergency function monitoring system	Automatic self test
Emergency power supply system	Peripheral (individual battery)
Battery technology	Lithium-ion
Type of lithium-ion battery	Lithium iron phosphate (LiFePO4)
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Plastic
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	230 - 230 V
Light distributor	Diffuser lens/optic/panel
Degree of protection (IP)	IP65
Impact strength	IK08
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	0 - 40 °C
Luminous flux in emergency mode	500 lm
Rated luminous flux according to IEC 62722-2- 1	500 - 500 lm
Max. system power	24 W
Power consumption in emergency mode	1.9 W
Colour temperature	4000 - 4000 K
Nominal operation time	1 - 8 h
Width	325 mm

INFINITA RTI IP65 NOT PERMANENT CBL LTO XL

	B19451
Height/depth	45 mm
Length	130 mm
Built-in width	132 mm
Built-in height/depth	45 mm
Built-in length	326 mm

Brand	BEGHELLI
Art. N°	B19451
Sales unit	pc
EAN PCE	8002219749062
EAN QTY PCE	1
EAN C01	8002219849069
EAN QTY C01	1
Intrastat code	85393110