

Luminaire

PRATICA IP65 300L SE AT

B250ATSE



PRATICA IP65 300L SE AT

	B250ATSE
Function	Escape route lighting
Emergency function monitoring system	Automatic self test
Emergency power supply system	Peripheral (individual battery)
Battery technology	Lithium-ion
Type of lithium-ion battery	Lithium iron phosphate (LiFePO4)
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Plastic
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	230 - 4000 V
Light distributor	Diffuser lens/optic/panel
Degree of protection (IP)	IP65
Impact strength	IK08
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	0 - 8 °C
Luminous flux in emergency mode	300 lm
Max. system power	2.6 W
Power consumption in emergency mode	2.6 W
Colour temperature	4000 - 40 K
Recognition distance	24 m
Nominal operation time	1 h
Width	300 mm
Height/depth	55 mm

PRATICA IP65 300L SE AT

	B250ATSE
Length	138 mm
Brand	BEGHELLI
Art. N°	B250ATSE
Sales unit	pc
EAN PCE	8002219745545
EAN QTY PCE	1
EAN C01	8002219845542
EAN QTY C01	12
Intrastat code	85393110