

# Luminaire

## DOWNLIGHT LED 8W 4000K A++

B71051



DOWN LED 8W 720Lm 4.000K

|                                                      | B71051                                  |
|------------------------------------------------------|-----------------------------------------|
| Lamp type                                            | LED not exchangeable                    |
| With light source                                    | Yes                                     |
| Housing material                                     | Plastic                                 |
| Housing colour                                       | White                                   |
| Material cover                                       | Other                                   |
| Voltage type                                         | AC                                      |
| Nominal voltage                                      | 230 - 230 V                             |
| Type of control gear                                 | LED operating device current-controlled |
| With control gear                                    | Yes                                     |
| Light distribution                                   | Symmetric                               |
| Beam angle                                           | > 80° - Extreme wide beam               |
| Colour consistency (McAdam ellipse)                  | SDCM3                                   |
| Light outlet                                         | Direct                                  |
| Degree of protection (IP), front side                | IP40                                    |
| Impact strength                                      | IK05                                    |
| Protection class according to IEC 61140              | II                                      |
| Emergency power supply system                        | None                                    |
| Rated ambient temperature according to IEC 62722-2-1 | -20 - 40 °C                             |
| Filament test according to IEC 60695-2-11            | 650 °C - 30 s                           |
| Luminaire efficacy                                   | 90 - 90 lm/W                            |
| Max. system power                                    | 8 W                                     |
| Rated luminous flux according to IEC 62722-2- 1      | 720 - 720 lm                            |
| Colour of light                                      | White                                   |
| Colour temperature                                   | 4000 - 4000 K                           |
| Colour rendering index CRI                           | 80-89                                   |

## DOWNLIGHT LED 8W 4000K A++

|                |               |
|----------------|---------------|
|                | <b>B71051</b> |
| Height/depth   | 30 mm         |
| Outer diameter | 85 mm         |

|                |               |
|----------------|---------------|
| Brand          | BEGHELLI      |
| Art. N°        | B71051        |
| Sales unit     | pc            |
| EAN PCE        | 8002219822703 |
| EAN QTY PCE    | 1             |
| EAN C01        | 8002219822703 |
| EAN QTY C01    | 12            |
| EAN C02        | 8002219950604 |
| EAN QTY C02    | 60            |
| Intrastat code | 94051940      |