

Luminaires

DOWNLIGHT COMP.LED 15W 4000K A++

B71055


DW LED 15W 1.350Lm 4.000K

	B71055
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Plastic
Housing colour	White
Material cover	Plastic, opal
Voltage type	AC
Nominal voltage	230 - 230 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Beam angle	> 80° - Extreme wide beam
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	60000 h
Degree of protection (IP), front side	IP40
Impact strength	IK05
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C
Filament test according to IEC 60695-2-11	650 °C - 30 s
Luminaire efficacy	90 - 90 lm/W
Max. system power	15 W
Rated luminous flux according to IEC 62722-2- 1	1350 - 1350 lm
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Height/depth	60 mm

DOWNLIGHT COMP.LED 15W 4000K A++

	B71055
Outer diameter	150 mm
Built-in height/depth	60 mm
Colour of light adjustable	No
Luminous flux adjustable	No
Beam angle adjustable	No

Brand	BEGHELLI
Art. N°	B71055
Sales unit	pc
EAN PCE	8002219722744
EAN QTY PCE	1
EAN QTY C01	12
Intrastat code	94051940