

Luminaire

DOWNLIGHT COMP.LED 25W 4000K A++

B71057



DW LED 25W 2.250Lm 4.000K

	B71057
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing colour	White
Type of grid	White
Voltage type	AC
Nominal voltage	230 - 230 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	60000 h
Degree of protection (IP), rear side	IP42
Degree of protection (IP), front side	IP40
Impact strength	IK05
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C
Filament test according to IEC 60695-2-11	650 °C - 30 s
Luminaire efficacy	90 - 90 lm/W
Max. system power	25 W
Rated luminous flux according to IEC 62722-2- 1	2250 - 2250 lm
Colour of light	White

DOWNLIGHT COMP.LED 25W 4000K A++

	B71057
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Height/depth	60 mm
Outer diameter	200 mm
Built-in height/depth	60 mm
Total harmonic distortion (THD)	0.55 %

Brand	BEGHELLI
Art. N°	B71057
Sales unit	pc
EAN PCE	8002219822765
EAN QTY PCE	1
EAN C01	8002219822765
EAN QTY C01	12
Intrastat code	94051940