

Luminaires

F65 LED 11W IP65 ATRIPARA SA123H

BR1124SA



F65 LED 24W IP65 AT SA LF

	BR1124SA
Mounting method	Wall surface mounting/ceiling surface mounting
Function	Escape route lighting/signage
Suitable for labelling type	Sticker
Type of indicator	Single-sided
With pictogram	Yes
Suitable for standby switching	Yes
Suitable for continuous circuit	Yes
With remote switch connection	Yes
Emergency function monitoring system	Automatic self test
Emergency power supply system	Peripheral (individual battery)
Battery technology	Lithium-ion
Type of lithium-ion battery	Lithium iron phosphate (LiFePO4)
With heating element for battery	No
Lamp type	LED not exchangeable
With light source	Yes
Suitable for number of light sources	1
Lamp holder	None
Number of lighting heads	1
Housing material	Plastic
RAL-number housing	9003
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	230 - 230 V
Type of control gear	LED operating device current-controlled

F65 LED 11W IP65 ATRIPARA SA123H

	BR1124SA
Light distributor	Diffuser lens/optic/panel
Constant light output (CLO)	No
Degree of protection (IP)	IP65
Impact strength	IK07
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	0 - 40 °C
Luminous flux in emergency mode	450 lm
Rated luminous flux according to IEC 62722-2- 1	250 - 250 lm
Max. system power	4 W
Power consumption in emergency mode	4 W
Luminous flux in standby mode	250 lm
Colour temperature	4000 - 4000 K
Power factor	0.1
Recognition distance	25 m
Nominal operation time	1 - 8 h
Width	354 mm
Height/depth	49 mm
Length	152 mm
Built-in height/depth	49 mm

Brand	BEGHELLI
Art. N°	BR1124SA
Sales unit	pc
EAN PCE	8002219509116
EAN QTY PCE	1
EAN C01	8002219609113
EAN QTY C01	12
Intrastat code	85393110