

Luminaires

F65 LED 11W IP65 ATRIPARA SE123H

BR1124



F65 LED 24W IP65 AT SE LF

	BR1124
Mounting method	Surface mounting/recessed mounting
Function	Escape route lighting
Suitable for labelling type	Sticker
Type of indicator	Single-sided
With pictogram	No
Suitable for standby switching	Yes
Suitable for continuous circuit	No
With remote switch connection	Yes
Emergency function monitoring system	Automatic self test
Emergency power supply system	Peripheral (individual battery)
Battery technology	Lithium-ion
Type of lithium-ion battery	Lithium iron phosphate (LiFePO4)
With heating element for battery	No
Lamp type	LED not exchangeable
With light source	Yes
Suitable for number of light sources	1
Lamp holder	None
Number of lighting heads	1
Housing material	Plastic
RAL-number housing	9003
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	207 - 253 V
Type of control gear	Electronic ballast

F65 LED 11W IP65 ATRIPARA SE123H

	BR1124
Light distributor	Diffuser lens/optic/panel
Degree of protection (IP)	IP65
Impact strength	IK07
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	0 - 40 °C
Luminous flux in emergency mode	450 lm
Rated luminous flux according to IEC 62722-2- 1	70 - 450 lm
Max. system power	1.9 W
Colour temperature	4000 - 4000 K
Power factor	0.05
Recognition distance	25 m
Nominal operation time	1 - 8 h
Width	354 mm
Height/depth	49 mm
Length	152 mm

Brand	BEGHELLI
Art. N°	BR1124
Sales unit	pc
EAN PCE	8002219609106
EAN QTY PCE	1
EAN C01	8002219609106
EAN QTY C01	12
Intrastat code	85393110