

Luminaire

F65LED24W IP65 ATRIPARA SA123H

BR2436SA



F65 LED 36W IP65 AT SA LF

	BR2436SA
Mounting method	Wall surface mounting/ceiling surface mounting
Function	Escape route lighting/signage
Suitable for labelling type	Sticker
Type of indicator	Single-sided
With pictogram	Yes
Suitable for standby switching	Yes
Suitable for continuous circuit	Yes
With remote switch connection	Yes
Emergency function monitoring system	Automatic self test
Emergency power supply system	Peripheral (individual battery)
Battery technology	Lithium-ion
Type of lithium-ion battery	Lithium iron phosphate (LiFePO4)
With heating element for battery	No
Lamp type	LED not exchangeable
With light source	Yes
Suitable for number of light sources	1
Lamp holder	None
Number of lighting heads	1
Housing material	Plastic
Housing colour	Blue
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	207 - 253 V
Type of control gear	LED operating device current-controlled
Light distributor	Diffuser lens/optic/panel

F65LED24W IP65 ATRIPARA SA123H

	BR2436SA
Constant light output (CLO)	No
Degree of protection (IP)	IP65
Impact strength	IK07
Protection class according to IEC 61140	II
Luminous flux in emergency mode	700 lm
Rated luminous flux according to IEC 62722-2- 1	100 - 700 lm
Max. system power	4 W
Power consumption in emergency mode	4 W
Luminous flux in standby mode	250 lm
Colour temperature	4000 - 4000 K
Power factor	0.1
Recognition distance	25 m
Nominal operation time	1 - 8 h
Width	354 mm
Height/depth	49 mm
Length	152 mm

Brand	BEGHELLI
Art. N°	BR2436SA
Sales unit	pc
EAN PCE	8002219609137
EAN QTY PCE	1
EAN C01	8002219609137
EAN QTY C01	12
Intrastat code	94051940