

Luminaires

F65LED24W IP65 ATRIPARA SE123H

BR2436

F65 LED 36W IP65 AT SE LF

	BR2436
Mounting method	Wall surface mounting/ceiling surface mounting
Function	Escape route lighting/signage
Suitable for labelling type	Insert sheet/plate
Type of indicator	Single/double-sided
With pictogram	No
Suitable for standby switching	Yes
Suitable for continuous circuit	No
With remote switch connection	Yes
With remote control	No
Emergency function monitoring system	Automatic self test
Emergency power supply system	Peripheral (individual battery)
Battery technology	Lithium-ion
Type of lithium-ion battery	Lithium iron phosphate (LiFePO4)
With heating element for battery	No
Lamp type	LED not exchangeable
With light source	Yes
Suitable for number of light sources	1
Lamp holder	None
Number of lighting heads	1
Housing material	Plastic
RAL-number housing	9003
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	207 - 253 V

F65LED24W IP65 ATRIPARA SE123H

	BR2436
Type of control gear	LED operating device current-controlled
Exchangeable control gear	No
Light distributor	Diffuser lens/optic/panel
Constant light output (CLO)	No
Degree of protection (IP)	IP65
Impact strength	IK07
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	0 - 40 °C
Luminous flux in emergency mode	700 lm
Rated luminous flux according to IEC 62722-2- 1	100 - 700 lm
Max. system power	16 W
Power consumption in emergency mode	1.9 W
Luminous flux in standby mode	0 lm
Colour temperature	4000 - 4000 K
Power factor	0.05
Recognition distance	25 m
Nominal operation time	1 - 8 h
Width	354 mm
Height/depth	49 mm
Length	152 mm

Brand	BEGHELLI
Art. N°	BR2436
Sales unit	pc
EAN PCE	8002219509123
EAN QTY PCE	1
EAN QTY C01	12
Intrastat code	94051940