

DICROICALED TRP DIMMABLE



Code	21714
Lighting technology used:	LED
Non-directional or directional (NDLS / DLS):	DLS
Light source cap-type (or other electric interface):	GU10
Mains or non-mains (MLS / NMLS):	MLS
Dimmable:	yes
On-mode power (Pon), expressed in W	7,5 (W)
Energy consumption (kWh/1000 h)	7 (kWh/1000h)
Energy efficiency class	F
Useful luminous flux (Φuse)	600 in narrow cone (90°)
Correlated colour temperature K	3000

Height	56 (mm)
Width	50 (mm)
Depth	50 (mm)
Claim of equivalent powerc	yes
If yes, equivalent power (W)	83 (W)
Chromaticity coordinates (x and y)	
X	0,434
Y	0,397
Peak luminous intensity (cd)	995 (cd)
Beam angle in degrees, or the range of beam angles that can be set	38 (°)
R9 colour rendering index value	4
Survival factor	0,9
Lumen maintenance factor	0,96
displacement factor (cos φ1)	0,5
Colour consistency in McAdam ellipses	5
Flicker metric (Pst LM)	1
Stroboscopic effect metric (SVM)	0,4



MARINO CRISTAL SPA
Via Guardia del Consiglio, 29/31
47899 - Serravalle
REPUBBLICA DI SAN MARINO

TEL +378 0549 901188
FAX +378 0549 900612
www.marinocristal.com
marinocristal@marinocristal.com

