

DATA SHEET

ANGEL: 700 lumen solar LED wall light with double light beam.
White



PACKING	INNER	MASTER
	 pcs	 pcs
Colour box	6	48



TECHNICAL DATA	
Name	ANGEL
Power supply	SOLAR
Power supply provided	YES
Type of power supply provided	SOLAR PANEL
Batteries provided	(INCLUDED)
Battery type	18650
Battery capacity (mAh)	2000
Stack technology	LITHIUM-ION
How many batteries are used	1
Charging time (h)	8
Battery/battery weight (kg)	0.050
Maximum autonomy (h)	8
Lighting source	SMD LED
Lighting power (W)	5
Lumen	700
Light beam	DIFFUSE
Beam angle (°)	270°
Installation height (meters)	3-5 METERS
Material	ABS + PC
Color	WHITE
Switch	YES
IP Protection	IP54
Insulation class	III
Light colour	4000K
Rated voltage (V)	3,7
Warranty	2 YEARS
Width (mm)	175
Depth (mm)	124
Height (mm)	50
Net weight (Kg)	0.430

DESCRIPTION

Solar LED Wall Light: Classic, simple, beautiful. 700 lumen LED outdoor solar light with double beam Up & Down Light effect, splendid light effects that create a wonderful atmosphere in front of the house or in the garden. The lamp mounts the latest generation SMD LEDs with high-performance diffuser: the light is homogeneous; 4000K light: neither too warm nor too cold. Solar light: This solar lamp with Up&Down effect recharges during the day with solar energy and lights up automatically in the dark or at night. It is powered by solar energy: it does not require wiring and uses free and eternally renewable energy. It is recommended to install it in particularly sunny areas so as to recharge the batteries to their maximum capacity and thus enjoy a unique show at night! Solar LED wall light in anti-UV polycarbonate and ABS; contemporary and extremely refined design; IP44: it is resistant to shocks and atmospheric agents; the electronic part is particularly resistant to water. Operation: The lamp recharges during the day, using solar rays. 4 modes of use: continuous lighting at 25% / 50% / 75% / 100%. It also allows you to manage the battery life. Equipped with a 1.7W monocrystalline solar panel and a 2000mAh Li-Ion battery that guarantees up to 8 hours of battery life (depending on the charge received during the day), well above market standards. It can be fixed using dowels (provided).

Packing type	Colour box
Pack length (mm)	140
Pack width (mm)	180
Pack height (mm)	55
Packed product weight (kg)	26.600
Inner width (cm)	40
Inner length (cm)	38
Inner height (cm)	15
Quantity in inner	6
Gross weight inner (kg)	3.200
ITF INNER	18003910116082
Master length (cm)	40
Master width (cm)	40
Master height (cm)	63
Quantity in master	48
Master gross weight (kg)	26.600
ITF MASTER	28003910116089
How many pieces on 80x120 pallet (pz)	576
INTRASTAT Code	94055000
DEEE	0.08

