

Luminaires

GRACE BLC LED 7W/3000K IP44

ARI-50331



GRACE BLC LED 7W/3000K IP44

	ARI-50331
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Plastic
Housing colour	White
Material cover	Plastic, opal
Voltage type	AC
Nominal voltage	220 - 240 V
Nominal current	60 - 60 mA
Type of control gear	LED operating device current-controlled
With control gear	Yes
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	30000 h
Degree of protection (IP), rear side	IP20
Degree of protection (IP), front side	IP44
Impact strength	IK02
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	-20 - 35 °C
With presence detector	Yes
With movement sensor	Yes
Filament test according to IEC 60695-2-11	650 °C - 30 s
Suitable for lamp power	7 - 7 W

GRACE BLC LED 7W/3000K IP44

	ARI-50331
Luminaire efficacy	91.3 - 91.3 lm/W
Max. system power	6.9 W
Rated luminous flux according to IEC 62722-2- 1	630 - 630 lm
Colour of light	White
Colour temperature	3000 - 3000 K
Height/depth	64 mm
Outer diameter	92 mm
Photobiological safety according to EN 62471	RG0
Colour of light adjustable	No
Luminous flux adjustable	No
Beam angle adjustable	No

Brand	ARIC
Art. N°	ARI-50331
Sales unit	pc
EAN PCE	3170070503316
EAN QTY PCE	1
Intrastat code	94051190