



Pannelli LED


PAN LED 45W 60X60 UGR<19 3K

Order code 70044

EAN 8002219738042

Technical specifications

Absorbed Power	45 W
Supply voltage type	AC
Nominal voltage (AC)	230 Vac
Ambient temperature (min)	-20 °C
Ambient temperature (max)	40 °C
Insulation class	II
CCT light tone	3000 K
Optical protection grade	IP40
LED number	192
Colour consistency	SDCM3
Colour trim	White
CRI color rendering	>80
Driver type	ED
Ballast	For constant current LED
Efficiency	95 lm/W
Equivalent power	4x18w
Frequency (max)	60 Hz
Frequency (min)	50 Hz
Power factor	0.95
Glow wire strength	650 °C - 30s.
MTBF driver	30000 h
Luminaire flux	4275 lm
Mounting	Recessed, False Ceiling Recessed
Trim material	Aluminum
UGR	19
Voltage supply range (max)	253 V
Voltage supply range (min)	207 V




Installation and applications

Environment	Offices
Application	Offices, Shops

Mechanical specifications

Height	9 mm
Length	595 mm
Width	595 mm
Weight	3.7 Kg
Body material	White Lacquered Aluminium
Colour housing	White
Cover material	Opal White Methacrylate



Box protection grade	IP20
Protection grade IP	IP20/IP40
Protection grade IK	IK05

Certifications and norms

UK SI 2021 No. 1095, EN IEC 55015:2019 + A11:2020, EN IEC 61000-3-2 :2019, EN 61547:2009, EN 62471:2008, EN IEC 60598-1:2021, EN 60598-2-2:2012, EN IEC 63000:2018, EN 62493:2010, EN 61000-3-3:2013

Accessories



20089
CORNICE PLAF BACKLITE
600X600



19359
INV P&L LED SE/SA 3H 20-60V



70049
CLIPS UNIVERSALE CGESSO
M600



19358
INV P&L LED SE/SA 1H 20-60V



70033
SUSPENSION WIRE PANELED