



X-Six SQ LED - CCT

X-SIX SQ LED CCT MULTIPOWER M

Versatile appliance designed for both recessed and ceiling installation with a quick bayonet bracket. Equipped with CCT function with 3 different color temperatures that can be adjusted using the selector located on the back of the unit. All accessories are included in the packaging.



Order code 71067

EAN 8002219887498

Technical specifications

Absorbed Power	12 W, 18 W, 24 W
Supply voltage type	AC
Nominal voltage (AC)	230 Vac
Ambient temperature (min)	-20 °C
Ambient temperature (max)	40 °C
Insulation class	II
CCT light tone	3000 K, 4000 K, 6000 K
CCT (max)	6000 K
CCT (min)	3000 K
LED number	150
Beam angle	120 °
Colour consistency	SDCM3
CRI color rendering	>80
Ballast	For constant current LED
Efficiency	90 lm/W
Frequency (max)	60 Hz
Frequency (min)	50 Hz
Power factor	0.55
Glow wire strength	550 °C - 30s.
MTBF driver	30000 h
Luminaire flux	1080 lm, 1620 lm, 2160 lm
Mounting	Ceiling, Recessed
Voltage supply range (max)	253 V
Voltage supply range (min)	207 V





Installation and applications

Environment	Offices
Application	Offices, Condos, Commercial Areas, Hotels, Malls, Shops



Mechanical specifications

Height	20 mm
Length	300 mm
Width	300 mm
Weight	0.5 Kg
Colour housing	White
Protection grade IP	IP20
Protection grade IK	IK05



Foro di incasso 205x205 mm

Certifications and norms

UK SI 2021 No. 1095, EN 62471:2008, EN IEC 60598-1:2021, EN 60598-2-2:2012, EN IEC 63000:2018, EN 62493:2010, EN 61000-3-3:2013, REG. 2019/2020(EU), EN IEC 55015:2019 + A11:2020, EN IEC 61000-3-2 :2019

