

Luminaire

LOG LED LGFM 8W SA 2/4/6N 750LM

B12185FM



	B12185FM
Mounting method	Surface mounting/recessed mounting
Function	Escape route lighting
Emergency function monitoring system	Automatic self test
Emergency power supply system	Peripheral (individual battery)
Battery technology	NiMH
Lamp type	LED not exchangeable
With light source	Yes
Lamp holder	None
Housing material	Plastic
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	230 - 230 V
Type of control gear	LED operating device current-controlled
Light distributor	Reflector
Degree of protection (IP)	IP65
Impact strength	IK08
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	0 - 40 °C
Luminous flux in emergency mode	750 lm
Rated luminous flux according to IEC 62722-2- 1	750 - 750 lm
Max. system power	9 W
Power consumption in emergency mode	9 W
Luminous flux in standby mode	400 lm
Colour temperature	5000 - 5000 K
Recognition distance	20 m

LOG LED LGFM 8W SA 2/4/6N 750LM

	B12185FM
Nominal operation time	2 - 6 h
Width	406 mm
Height/depth	63 mm
Length	147 mm

Brand	BEGHELLI
Art. N°	B12185FM
Sales unit	pc
EAN PCE	5413180115405;8002219504210
EAN QTY PCE	1
EAN C01	8002219604217
EAN QTY C01	6
Intrastat code	85393110