

Luminaire

STILE IN LED 11W SE 6 LF

B1499



STILE IN LED 11W SE 6 LF

	B1499
Mounting method	Built-in
Function	Escape route lighting
Emergency power supply system	Peripheral (individual battery)
Battery technology	Lithium-ion
Type of lithium-ion battery	Lithium iron phosphate (LiFePO4)
Lamp type	LED not exchangeable
With light source	Yes
Lamp holder	None
Housing material	Plastic
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	230 - 230 V
Light distributor	Diffuser lens/optic/panel
Degree of protection (IP)	IP40
Impact strength	IK05
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	0 - 40 °C
Luminous flux in emergency mode	120 lm
Rated luminous flux according to IEC 62722-2- 1	130 - 130 lm
Max. system power	11 W
Power consumption in emergency mode	2 W
Colour temperature	4000 - 4000 K
Recognition distance	15 m
Nominal operation time	6 - 6 h

STILE IN LED 11W SE 6 LF

	B1499
Width	292 mm
Height/depth	55 mm
Length	102 mm

Brand	BEGHELLI
Art. N°	B1499
Sales unit	pc
EAN PCE	8002219597809
EAN QTY PCE	1
Intrastat code	85393110