

Luminaire

P.MODULA 300 IP65 CT SA/SE

B18741



P.MODULA 300 IP65 CT SA/SE

	B18741
Mounting method	Surface mounting/recessed mounting
With pictogram	Yes
Emergency function monitoring system	Automatic self test
Emergency power supply system	Peripheral (individual battery)
Battery technology	Lithium-ion
Type of lithium-ion battery	Lithium iron phosphate (LiFePO4)
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Plastic
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	230 - 4000 V
Light distributor	Reflector
Degree of protection (IP)	IP65
Impact strength	IK07
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	0 - 8 °C
Luminous flux in emergency mode	300 lm
Max. system power	6 W
Power consumption in emergency mode	6 W
Luminous flux in standby mode	300 lm
Colour temperature	4000 - 50 K
Recognition distance	21 m
Nominal operation time	1 h

P.MODULA 300 IP65 CT SA/SE

	B18741
Width	119 mm
Height/depth	38 mm
Length	265 mm
Built-in width	120 mm
Built-in height/depth	38 mm
Built-in length	300 mm

Brand	BEGHELLI
Art. N°	B18741
Sales unit	pc
EAN PCE	8002219887306
EAN QTY PCE	1
EAN C01	8002219887313
EAN QTY C01	4
Intrastat code	85393110