

# Luminaire

## F65 LED 24W IP65 SE 1/3 LF

B19206N



F65 LED 24W IP65 SE 1/3 LF

|                                      | B19206N                            |
|--------------------------------------|------------------------------------|
| Mounting method                      | Surface mounting/recessed mounting |
| Function                             | Escape route lighting              |
| Type of indicator                    | Single-sided                       |
| With pictogram                       | No                                 |
| Suitable for standby switching       | Yes                                |
| Suitable for continuous circuit      | No                                 |
| With remote switch connection        | Yes                                |
| With remote control                  | Yes                                |
| Emergency function monitoring system | Automatic self test                |
| Emergency power supply system        | Peripheral (individual battery)    |
| Battery technology                   | Lithium-ion                        |
| Type of lithium-ion battery          | Lithium iron phosphate (LiFePO4)   |
| With heating element for battery     | No                                 |
| Lamp type                            | LED not exchangeable               |
| With light source                    | Yes                                |
| Suitable for number of light sources | 1                                  |
| Lamp holder                          | None                               |
| Number of lighting heads             | 1                                  |
| Housing material                     | Plastic                            |
| RAL-number housing                   | 9003                               |
| Housing colour                       | White                              |
| Material cover                       | Plastic, transparent               |
| Voltage type                         | AC                                 |
| Nominal voltage                      | 230 - 230 V                        |
| Type of control gear                 | Electronic ballast                 |

## F65 LED 24W IP65 SE 1/3 LF

|                                                      |                           |
|------------------------------------------------------|---------------------------|
|                                                      | <b>B19206N</b>            |
| Exchangeable control gear                            | Yes                       |
| Light distributor                                    | Diffuser lens/optic/panel |
| Degree of protection (IP)                            | IP65                      |
| Impact strength                                      | IK07                      |
| Protection class according to IEC 61140              | II                        |
| Rated ambient temperature according to IEC 62722-2-1 | 0 - 40 °C                 |
| Luminous flux in emergency mode                      | 450 lm                    |
| Max. system power                                    | 2.6 W                     |
| Colour temperature                                   | 4000 - 4000 K             |
| Power factor                                         | 0.06                      |
| Recognition distance                                 | 25 m                      |
| Nominal operation time                               | 1 - 3 h                   |
| Width                                                | 354 mm                    |

  

|                |               |
|----------------|---------------|
| Brand          | BEGHELLI      |
| Art. N°        | B19206N       |
| Sales unit     | pc            |
| EAN PCE        | 8002219878779 |
| EAN QTY PCE    | 1             |
| Intrastat code | 85393110      |