

Luminaire

DOT AE SE/SA 1/2/3H IP65 RM

B19700



DOT AE SE/SA 1/2/3H IP65 RM

	B19700
Mounting method	Built-in
Function	Escape route lighting
Emergency power supply system	Peripheral (individual battery)
Battery technology	Lithium-ion
Type of lithium-ion battery	Lithium iron phosphate (LiFePO4)
Lamp type	LED not exchangeable
With light source	Yes
Lamp holder	None
Housing material	Plastic
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	230 - 230 V
Light distributor	Diffuser lens/optic/panel
Degree of protection (IP)	IP65
Impact strength	IK07
Protection class according to IEC 61140	I
Rated ambient temperature according to IEC 62722-2-1	0 - 40 °C
Luminous flux in emergency mode	550 lm
Rated luminous flux according to IEC 62722-2- 1	240 - 240 lm
Max. system power	2.5 W
Power consumption in emergency mode	2.5 W
Luminous flux in standby mode	240 lm
Colour temperature	4000 - 4000 K
Nominal operation time	1 - 3 h

DOT AE SE/SA 1/2/3H IP65 RM

	B19700
Width	80 mm
Height/depth	40 mm
Length	80 mm
Outer diameter	80 mm
Built-in width	60 mm
Built-in height/depth	40 mm
Built-in length	60 mm
Built-in diameter	60 mm

Brand	BEGHELLI
Art. N°	B19700
Sales unit	pc
EAN PCE	8002219869159
EAN QTY PCE	1
Intrastat code	94051940