

Luminaires

IRONFLAG CT 30M SA LF TO THE RIGHT

B19811



IRONFLAG CT 30M SA LF

	B19811
With pictogram	Yes
Emergency function monitoring system	Automatic self test
Emergency power supply system	Peripheral (individual battery)
Battery technology	Lithium-ion
Type of lithium-ion battery	Lithium iron phosphate (LiFePO4)
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Aluminium
Housing colour	Aluminium
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	230 - 230 V
Light distributor	Diffuser lens/optic/panel
Degree of protection (IP)	IP42
Impact strength	IK05
Rated ambient temperature according to IEC 62722-2-1	0 - 40 °C
Luminous flux in emergency mode	50 lm
Max. system power	4 W
Power consumption in emergency mode	4 W
Colour temperature	4000 - 4000 K
Recognition distance	30 m
Nominal operation time	1 - 8 h
Width	210 mm
Height/depth	45 mm
Length	330 mm

IRONFLAG CT 30M SA LF TO THE RIGHT

Brand	BEGHELLI
Art. N°	B19811
Sales unit	pc
EAN PCE	8002219869630
EAN QTY PCE	1
Intrastat code	85393110