

Luminaire

BS100 LED 2X36 4000K

B236SD



BS100 LED 2X36 SD 4000K

	B236SD
Suitable for suspended mounting	Yes
Suitable for ceiling mounting	Yes
Suitable for surface mounting	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Plastic
Housing colour	Grey
Type of grid	None
Voltage type	AC/DC
Nominal voltage	93 - 265 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Dimmable	Yes
Light distributor	Reflector
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Degree of protection (IP), front side	IP65
Impact strength	IK05
Emergency power supply system	None
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C
With light sensor	Yes
Filament test according to IEC 60695-2-11	850 °C - 30 s
Luminaire efficacy	133 - 133 lm/W
Max. system power	46 W
Rated luminous flux according to IEC 62722-2- 1	6100 - 6100 lm

BS100 LED 2X36 4000K

	B236SD
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Width	170 mm
Height/depth	95 mm
Length	1280 mm
Photobiological safety according to EN 62471	RG0

Brand	BEGHELLI
Art. N°	B236SD
Sales unit	pc
EAN PCE	8002219723574
EAN QTY PCE	1
Intrastat code	85392992