

Luminaire

BS100 LED REGLABLE HV M1280 4K 8000LM

B40004H



BS100 LED ADJUSTABLE HV M1280 4K 8000LM

	B40004H
Suitable for wall mounting	Yes
Suitable for suspended mounting	Yes
Suitable for ceiling mounting	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Plastic
Housing colour	Grey
Material cover	Plastic, opal
Voltage type	AC
Nominal voltage	230 - 230 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Dimmable	Yes
Light distributor	Reflector
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Energy efficiency class of the light source according to EU regulation 2019/2015	D
Rated lifetime L70/B50 at 25 °C	199000 h
Degree of protection (IP), front side	IP65
Impact strength	IK05
Protection class according to IEC 61140	I
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C
Filament test according to IEC 60695-2-11	850 °C - 30 s
Luminaire efficacy	157 - 179 lm/W
Max. system power	51 W
Rated luminous flux according to IEC 62722-2- 1	5000 - 8000 lm

BS100 LED REGLABLE HV M1280 4K 8000LM

	B40004H
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Width	170 mm
Height/depth	95 mm
Length	1280 mm
Total harmonic distortion (THD)	20 %
Photobiological safety according to EN 62471	RG0

Brand	BEGHELLI
Art. N°	B40004H
Sales unit	pc
EAN PCE	8002219889225
EAN QTY PCE	1
EAN QTY C01	6
Intrastat code	85393110