

Luminaires

BS100 LED REGLABLE LED HV L1580 4000K10000LM

B40005H



BS100 LED REG HV L1580 4K

	B40005H
Suitable for wall mounting	Yes
Suitable for suspended mounting	Yes
Suitable for ceiling mounting	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Plastic
Housing colour	Grey
Material cover	Plastic, opal
Voltage type	AC
Nominal voltage	230 - 230 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Light distributor	Reflector
Colour consistency (McAdam ellipse)	SDCM3
Energy efficiency class of the light source according to EU regulation 2019/2015	D
Rated lifetime L70/B50 at 25 °C	199000 h
Degree of protection (IP), front side	IP65
Impact strength	IK05
Protection class according to IEC 61140	I
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C
Filament test according to IEC 60695-2-11	850 °C - 30 s
Luminaire efficacy	159 - 171 lm/W
Max. system power	63 W
Rated luminous flux according to IEC 62722-2- 1	6000 - 10000 lm

BS100 LED REGLABLE LED HV L1580 4000K10000LM

	B40005H
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Width	170 mm
Height/depth	95 mm
Length	1580 mm
Total harmonic distortion (THD)	20 %
Photobiological safety according to EN 62471	RG0

Brand	BEGHELLI
Art. N°	B40005H
Sales unit	pc
EAN PCE	8002219889232
EAN QTY PCE	1
EAN QTY C01	6
Intrastat code	85393110