

Luminaires

L PAN 418 M600 U19 C90 ED 4K

B40101



L PAN 418 M600 U19 C90 ED 4K

	B40101
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Aluminium
Housing colour	White
Material cover	Plastic, transparent
Type of grid	White
Voltage type	AC
Nominal voltage	230 - 230 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Light distributor	Diffuser lens/optic/panel
Light distribution	Symmetric
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	50000 h
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq)	80 %
Degree of protection (IP), rear side	IP20
Degree of protection (IP), front side	IP40
Impact strength	IK05
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C
Filament test according to IEC 60695-2-11	650 °C - 30 s

L PAN 418 M600 U19 C90 ED 4K

	B40101
Luminaire efficacy	111 - 111 lm/W
Max. system power	36 W
Rated luminous flux according to IEC 62722-2- 1	4000 - 4000 lm
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	90-100
Width	595 mm
Height/depth	9 mm
Length	595 mm
Built-in length	595 mm
Built-in width	595 mm
Built-in height/depth	9 mm
Total harmonic distortion (THD)	5 %
Photobiological safety according to EN 62471	RG0

Brand	BEGHELLI
Art. N°	B40101
Sales unit	pc
EAN PCE	8002219755278
EAN QTY PCE	1
Intrastat code	85393110