

Luminaires

L PAN 258 30X120 U19C90 ED4K

B40137



LENSPAN 258 30X120 U19C90 ED4K

	B40137
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Suitable for workplace according to EN 12464-1	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Steel
Surface protection housing	Powder coating
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	230 - 230 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Light distributor	Diffuser lens/optic/panel
Light distribution	Symmetric
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Energy efficiency class of the light source according to EU regulation 2019/2015	E
Rated lifetime L70/B50 at 25 °C	160000 h
Degree of protection (IP), rear side	IP20
Degree of protection (IP), front side	IP40
Impact strength	IK05
Protection class according to IEC 61140	I
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C

L PAN 258 30X120 U19C90 ED4K

	B40137
Filament test according to IEC 60695-2-11	650 °C - 30 s
Luminaire efficacy	130 - 130 lm/W
Max. system power	50 W
Rated luminous flux according to IEC 62722-2- 1	6500 - 6500 lm
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	90-100
Width	296 mm
Height/depth	33 mm
Length	1196 mm
Built-in height/depth	33 mm
Photobiological safety according to EN 62471	RG0
Brand	BEGHELLI
Art. N°	B40137
Sales unit	pc
EAN PCE	8002219757500
EAN QTY PCE	1
Intrastat code	85393110