

Luminaires

L PAN 236 30X120 U19C90 SD4K

B40143



LENSPAN 236 30X120 U19C90 SD4K

	B40143
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Suitable for workplace according to EN 12464-1	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Steel
Surface protection housing	Powder coating
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC/DC
Nominal voltage	230 - 230 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Dimmable	Yes
Dimming programmable	Yes
Light distributor	Diffuser lens/optic/panel
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Energy efficiency class of the light source according to EU regulation 2019/2015	E
Rated lifetime L70/B50 at 25 °C	180000 h
Degree of protection (IP), rear side	IP20
Degree of protection (IP), front side	IP40
Impact strength	IK05
Protection class according to IEC 61140	II

L PAN 236 30X120 U19C90 SD4K

	B40143
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C
With light sensor	Yes
Filament test according to IEC 60695-2-11	650 °C - 30 s
Luminaire efficacy	129 - 129 lm/W
Max. system power	41 W
Rated luminous flux according to IEC 62722-2- 1	5300 - 5300 lm
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	90-100
Width	296 mm
Height/depth	44 mm
Length	1196 mm
Built-in length	1196 mm
Built-in width	296 mm
Built-in height/depth	44 mm
Total harmonic distortion (THD)	18 %
Photobiological safety according to EN 62471	RG0

Brand	BEGHELLI
Art. N°	B40143
Sales unit	pc
EAN PCE	8002219757562
EAN QTY PCE	1
Intrastat code	85393110