

Luminaire

ACCIAIO SDB L1500 4000K

B41229



ACCIAIO SDB L1500 4000K

	B41229
Suitable for ceiling mounting	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Steel
Housing colour	Grey
Voltage type	AC/DC
Nominal voltage	230 - 230 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Dimmable	Yes
Dimming DALI	Yes
Light distributor	Reflector
Light distribution	Symmetric
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Energy efficiency class of the light source according to EU regulation 2019/2015	C
Degree of protection (IP), front side	IP66
Max. number of luminaires per miniature circuit breaker B16 (MCB)	25
Impact strength	IK07
Protection class according to IEC 61140	I
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C
Filament test according to IEC 60695-2-11	850 °C - 30 s
Luminaire efficacy	151 - 151 lm/W
Max. system power	73 W

ACCIAIO SDB L1500 4000K

	B41229
Rated luminous flux according to IEC 62722-2- 1	11000 - 11000 lm
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Power factor	0.96
Width	108 mm
Height/depth	80 mm
Length	1535 mm
Photobiological safety according to EN 62471	RG0

Brand	BEGHELLI
Art. N°	B41229
Sales unit	pc
EAN PCE	8002219883254
EAN QTY PCE	1
Intrastat code	94051990