

Luminares

COMPLETA LED 24W AT SE LIFE

B4211



COMPLETA LED 24W AT SE LIFE

	B4211
Mounting method	Surface mounting/recessed mounting
Function	Escape route lighting/signage
Suitable for labelling type	Sticker
With pictogram	Yes
Suitable for standby switching	Yes
Suitable for continuous circuit	No
Emergency function monitoring system	Automatic self test
Emergency power supply system	Peripheral (individual battery)
Battery technology	Lithium-ion
Type of lithium-ion battery	Lithium iron phosphate (LiFePO4)
Lamp type	LED not exchangeable
With light source	Yes
Lamp holder	None
Housing material	Plastic
RAL-number housing	9003
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	230 - 230 V
Degree of protection (IP)	IP40
Impact strength	IK05
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	0 - 40 °C
Max. system power	1.9 W
Power consumption in emergency mode	1.9 W

COMPLETA LED 24W AT SE LIFE

	B4211
Colour temperature	4000 - 4000 K
Power factor	0.05
Recognition distance	15 m
Nominal operation time	1 - 8 h
Width	294 mm

Brand	BEGHELLI
Art. N°	B4211
Sales unit	pc
EAN PCE	8002219879509
EAN QTY PCE	1
Intrastat code	85393110