

Luminares

MULTI LENS GL AT SA LF

B4394



MULTI LENS GL AT SA LF

	B4394
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Plastic
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	230 - 230 V
Beam angle	Variable beam angle
Light outlet	Direct
Degree of protection (IP), rear side	IP20
Degree of protection (IP), front side	IP42
Impact strength	IK07
Protection class according to IEC 61140	II
Emergency power supply system	Peripheral (individual battery)
Rated ambient temperature according to IEC 62722-2-1	0 - 40 °C
Luminous flux in emergency mode	450 lm
Suitable for emergency lighting	Yes
Power consumption in emergency mode	5 W
Emergency function monitoring system	Automatic self test
With light sensor	Yes
Filament test according to IEC 60695-2-11	850 °C - 30 s
Rated luminous flux according to IEC 62722-2- 1	220 - 220 lm
Colour of light	White

MULTI LENS GL AT SA LF

	B4394
Colour temperature	4000 - 4000 K
Colour rendering index CRI	70-79
Height/depth	40 mm
Outer diameter	90 mm
Built-in diameter	60 mm
Photobiological safety according to EN 62471	RG0

Brand	BEGHELLI
Art. N°	B4394
Sales unit	pc
EAN PCE	8002219891990
EAN QTY PCE	1
EAN C01	8002219892003
EAN QTY C01	6