

Luminaires

PAN LED 36w 1200x300 3000K A++

B70012



PANNEL LED 1.200X300 38W 3.000K° 3.600Lm

	B70012
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Aluminium
Surface protection housing	Lacquered
Housing colour	White
Material cover	Plastic, opal
Type of grid	White
Voltage type	AC
Nominal voltage	230 - 3000 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Light distributor	Diffuser lens/optic/panel
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	100000 h
Degree of protection (IP), rear side	IP20
Degree of protection (IP), front side	IP40
Protection class according to IEC 61140	II
Emergency power supply system	None
Rated ambient temperature according to IEC 62722-2-1	-20 - 95 °C
Filament test according to IEC 60695-2-11	650 °C - 30 s
Luminaire efficacy	95 - 3600 lm/W
Max. system power	38 W

PAN LED 36w 1200x300 3000K A++

	B70012
Rated luminous flux according to IEC 62722-2- 1	3600 lm
Colour of light	White
Colour temperature	3000 - 40 K
Colour rendering index CRI	80-89
Width	295 mm
Height/depth	9 mm
Length	1195 mm
Colour of light adjustable	No
Luminous flux adjustable	No
Beam angle adjustable	No

Brand	BEGHELLI
Art. N°	B70012
Sales unit	pc
EAN PCE	8002219813312
EAN QTY PCE	1
EAN C01	8002219813312
EAN QTY C01	5
Intrastat code	94051940