

Luminaires

PANELED 600X600 45W 4.200Lm 4.000K

B70022



PANELED 600X600 45W 4.200Lm 4.000K

	B70022
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Aluminium
Surface protection housing	Lacquered
Housing colour	White
Material cover	Plastic, opal
Voltage type	AC
Nominal voltage	207 - 253 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	100000 h
Degree of protection (IP), rear side	IP20
Degree of protection (IP), front side	IP40
Impact strength	IK05
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C
Filament test according to IEC 60695-2-11	650 °C - 30 s
Luminaire efficacy	93 - 93 lm/W
Max. system power	45 W
Rated luminous flux according to IEC 62722-2- 1	4200 - 4200 lm
Colour of light	White

PANELED 600X600 45W 4.200Lm 4.000K

	B70022
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Width	595 mm
Height/depth	9 mm
Length	595 mm

Brand	BEGHELLI
Art. N°	B70022
Sales unit	pc
EAN PCE	8002219818546
EAN QTY PCE	1
EAN C01	8002219818546
EAN QTY C01	5
Intrastat code	94051940