

Luminaires

PAN LED 50W 1200x300 4000K

B70024



PANELED 1.200X300 45W 4.200Lm 4.000K

	B70024
Suitable for suspended mounting	Yes
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Suitable for surface mounting	Yes
Suitable for workplace according to EN 12464-1	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Aluminium
Surface protection housing	Powder coating
Housing colour	White
Material cover	Plastic, structured
Voltage type	AC
Nominal voltage	220 - 240 V
With control gear	Yes
Light distributor	Diffuser lens/optic/panel
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Degree of protection (IP), front side	IP40
Impact strength	IK05
Emergency power supply system	None
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C
Suitable for emergency lighting	Yes
Luminaire efficacy	93 - 93 lm/W

PAN LED 50W 1200x300 4000K

	B70024
Max. system power	45 W
Rated luminous flux according to IEC 62722-2- 1	4200 - 4200 lm
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Width	295 mm
Height/depth	9 mm
Length	1195 mm
Built-in length	1195 mm
Built-in width	295 mm
Built-in height/depth	46 mm

Brand	BEGHELLI
Art. N°	B70024
Sales unit	pc
EAN PCE	8002219818560
EAN QTY PCE	1
EAN C01	8002219818560
EAN QTY C01	5
Intrastat code	94051940