

Luminaires

PANELED 300X300mm 14W 4.000K 1.200LmA++.

B70038



PANELED 300X300mm 14W 4.000K 1.300Lm A++

	B70038
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Aluminium
Surface protection housing	Lacquered
Housing colour	White
Material cover	Plastic, opal
Voltage type	AC
Nominal voltage	230 - 230 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Light distribution	Symmetric
Beam angle	> 80° - Extreme wide beam
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	100000 h
Degree of protection (IP), rear side	IP20
Degree of protection (IP), front side	IP40
Impact strength	IK05
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C
Filament test according to IEC 60695-2-11	650 °C - 30 s
Luminaire efficacy	93 - 93 lm/W
Max. system power	14 W
Rated luminous flux according to IEC 62722-2- 1	1300 - 1300 lm
Colour of light	White

PANELED 300X300mm 14W 4.000K 1.200LmA++.

	B70038
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Width	295 mm
Height/depth	9 mm
Length	295 mm
Colour of light adjustable	No
Luminous flux adjustable	No
Beam angle adjustable	No

Brand	BEGHELLI
Art. N°	B70038
Sales unit	pc
EAN PCE	8002219729620
EAN QTY PCE	1
EAN C01	8002219829627
EAN QTY C01	5
Intrastat code	94051940