

Luminaires

LED PAN 45W UGR<19 600X600 4400Lm 3000K

B70044



PANELED 45W UGR

	B70044
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Suitable for workplace according to EN 12464-1	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Aluminium
Surface protection housing	Lacquered
Housing colour	White
Material cover	Plastic, opal
Type of grid	White
Voltage type	AC
Nominal voltage	230 - 230 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Light distributor	Diffuser lens/optic/panel
Light distribution	Symmetric
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	100000 h
Degree of protection (IP), rear side	IP20
Degree of protection (IP), front side	IP40
Impact strength	IK05
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C
Filament test according to IEC 60695-2-11	650 °C - 30 s

LED PAN 45W UGR<19 600X600 4400Lm 3000K

	B70044
Luminaire efficacy	95 - 95 lm/W
Max. system power	45 W
Rated luminous flux according to IEC 62722-2- 1	4275 - 4275 lm
Colour of light	White
Colour temperature	3000 - 3000 K
Colour rendering index CRI	80-89
Width	595 mm
Height/depth	9 mm
Length	595 mm
Built-in length	595 mm
Built-in width	595 mm
Built-in height/depth	9 mm
Brand	BEGHELLI
Art. N°	B70044
Sales unit	pc
EAN PCE	5413180114033
EAN QTY PCE	1
Intrastat code	94051940