

Luminaires

DOWNLIGHT COMP.LED 25W 3000K A++

B71056



DW LED 25W 2.250Lm 3.000K

	B71056
Suitable for ceiling mounting	Yes
With light source	Yes
Housing colour	White
Voltage type	AC
Nominal voltage	230 - 230 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Beam angle	> 80° - Extreme wide beam
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	60000 h
Degree of protection (IP), rear side	IP42
Degree of protection (IP), front side	IP40
Impact strength	IK05
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C
Filament test according to IEC 60695-2-11	650 °C - 30 s
Luminaire efficacy	90 - 90 lm/W
Max. system power	25 W
Rated luminous flux according to IEC 62722-2- 1	2250 - 2250 lm
Colour of light	White
Colour temperature	3000 - 3000 K
Colour rendering index CRI	80-89
Height/depth	60 mm
Outer diameter	200 mm

DOWNLIGHT COMP.LED 25W 3000K A++

Brand	BEGHELLI
Art. N°	B71056
Sales unit	pc
EAN PCE	8002219822758
EAN QTY PCE	1
EAN C01	8002219822758
EAN QTY C01	12
Intrastat code	94051940