

Luminaires

SAVING IP65 LED 2X36 4.400Lm 4.000K

B72010



SAVING IP65 LED 236 4.400Lm 4.000K

	B72010
Suitable for wall mounting	Yes
Suitable for suspended mounting	Yes
Suitable for ceiling mounting	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Plastic
Housing colour	Grey
Material cover	Plastic, structured
Voltage type	AC
Nominal voltage	230 - 230 V
Nominal current	200 - 200 mA
Type of control gear	LED operating device current-controlled
With control gear	Yes
Light distributor	Reflector
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Energy efficiency class of the light source according to EU regulation 2019/2015	D
Rated lifetime L70/B50 at 25 °C	180000 h
Degree of protection (IP), front side	IP65
Impact strength	IK05
Protection class according to IEC 61140	I
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C
Filament test according to IEC 60695-2-11	850 °C - 30 s
Luminaire efficacy	161 - 161 lm/W

SAVING IP65 LED 2X36 4.400Lm 4.000K

	B72010
Max. system power	28 W
Rated luminous flux according to IEC 62722-2- 1	4500 - 4500 lm
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Width	121 mm
Height/depth	82 mm
Length	1264 mm
Total harmonic distortion (THD)	20 %
Photobiological safety according to EN 62471	RG0

Brand	BEGHELLI
Art. N°	B72010
Sales unit	pc
EAN PCE	8002219728968
EAN QTY PCE	1
EAN QTY C01	6
Intrastat code	94051940