

Luminaires

SAVING IP65 LED 2X58 6.400Lm 4.000K

B72011



SAVING IP65 LED 2X58 6.400Lm 4.000K

	B72011
Suitable for wall mounting	Yes
Suitable for suspended mounting	Yes
Suitable for ceiling mounting	Yes
Suitable for surface mounting	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Plastic
Surface protection housing	Powder coating
Housing colour	Grey
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	230 - 230 V
Nominal current	300 - 300 mA
Type of control gear	LED operating device current-controlled
With control gear	Yes
Light distributor	Reflector
Colour consistency (McAdam ellipse)	SDCM3
Energy efficiency class of the light source according to EU regulation 2019/2015	D
Rated lifetime L70/B50 at 25 °C	199000 h
Degree of protection (IP), front side	IP65
Impact strength	IK05
Protection class according to IEC 61140	I
Emergency power supply system	None
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C

SAVING IP65 LED 2X58 6.400Lm 4.000K

	B72011
Filament test according to IEC 60695-2-11	850 °C - 30 s
Luminaire efficacy	155 - 155 lm/W
Max. system power	42 W
Rated luminous flux according to IEC 62722-2- 1	6500 - 6500 lm
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Width	121 mm
Height/depth	82 mm
Length	1264 mm
Total harmonic distortion (THD)	20 %
Photobiological safety according to EN 62471	RG0
Colour of light adjustable	No
Luminous flux adjustable	No
Beam angle adjustable	No

Brand	BEGHELLI
Art. N°	B72011
Sales unit	pc
EAN PCE	8002219728975
EAN QTY PCE	1
EAN QTY C01	6
Intrastat code	94051940