

# Luminaires

## ULTRATHIN DWL SQ LED 18W

**B75354**


### ULTRATHIN DWL SQ LED 18W

|                                                      | <b>B75354</b>                           |
|------------------------------------------------------|-----------------------------------------|
| Suitable for ceiling mounting                        | Yes                                     |
| Suitable for built-in mounting                       | Yes                                     |
| Lamp type                                            | LED not exchangeable                    |
| With light source                                    | Yes                                     |
| Housing colour                                       | White                                   |
| Voltage type                                         | AC                                      |
| Nominal voltage                                      | 230 - 230 V                             |
| Type of control gear                                 | LED operating device current-controlled |
| With control gear                                    | Yes                                     |
| Beam angle                                           | > 80° - Extreme wide beam               |
| Colour consistency (McAdam ellipse)                  | SDCM2                                   |
| Light outlet                                         | Direct                                  |
| Degree of protection (IP), rear side                 | IP20                                    |
| Degree of protection (IP), front side                | IP20                                    |
| Impact strength                                      | IK05                                    |
| Protection class according to IEC 61140              | II                                      |
| Rated ambient temperature according to IEC 62722-2-1 | -20 - 40 °C                             |
| Filament test according to IEC 60695-2-11            | 550 °C - 30 s                           |
| Luminaire efficacy                                   | 83 - 83 lm/W                            |
| Max. system power                                    | 18 W                                    |
| Rated luminous flux according to IEC 62722-2- 1      | 1500 - 1500 lm                          |
| Colour of light                                      | White                                   |
| Colour temperature                                   | 4000 - 4000 K                           |
| Colour rendering index CRI                           | 80-89                                   |
| Width                                                | 200 mm                                  |

## ULTRATHIN DWL SQ LED 18W

|                            |               |
|----------------------------|---------------|
|                            | <b>B75354</b> |
| Height/depth               | 25 mm         |
| Length                     | 200 mm        |
| Built-in length            | 200 mm        |
| Built-in width             | 200 mm        |
| Built-in height/depth      | 25 mm         |
| Colour of light adjustable | No            |

|                |               |
|----------------|---------------|
| Brand          | BEGHELLI      |
| Art. N°        | B75354        |
| Sales unit     | pc            |
| EAN PCE        | 8002219754851 |
| EAN QTY PCE    | 1             |
| Intrastat code | 85395200      |