

Luminaires

Modern and elegant design suitable for civil, commercial and industrial

B86152



FL LED 50W BIANCO IP65 4K

	B86152
With light source	Yes
Housing material	Aluminium
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	230 - 230 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Rated lifetime L70/B50 at 25 °C	50000 h
Degree of protection (IP), front side	IP66
Impact strength	IK07
Protection class according to IEC 61140	I
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C
Max. system power	50 W
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Rated luminous flux according to IEC 62722-2-1	5000 - 5000 lm
Luminaire efficacy	100 - 100 lm/W
Length	175 mm
Width	146 mm
Height/depth	33 mm
Filament test according to IEC 60695-2-11	960 °C - 30 s
Photobiological safety according to EN 62471	RG0

Modern and elegant design suitable for civil, commercial and
industri

Brand	BEGHELLI
Art. N°	B86152
Sales unit	pc
EAN PCE	8002219758897
EAN QTY PCE	1
EAN QTY C01	6
Intrastat code	94054910