

## Luminaires

Modern and elegant design suitable for civil, commercial and industrial

**B86159**



FL LED 50W BLACK IP65 3K

|                                                      | <b>B86159</b>                           |
|------------------------------------------------------|-----------------------------------------|
| Lamp type                                            | LED not exchangeable                    |
| With light source                                    | Yes                                     |
| Housing material                                     | Aluminium                               |
| Housing colour                                       | Black                                   |
| Voltage type                                         | AC                                      |
| Nominal voltage                                      | 230 - 230 V                             |
| Type of control gear                                 | LED operating device current-controlled |
| With control gear                                    | Yes                                     |
| Light outlet                                         | Direct                                  |
| Rated lifetime L70/B50 at 25 °C                      | 50000 h                                 |
| Degree of protection (IP), front side                | IP66                                    |
| Impact strength                                      | IK07                                    |
| Protection class according to IEC 61140              | I                                       |
| Rated ambient temperature according to IEC 62722-2-1 | -20 - 40 °C                             |
| Max. system power                                    | 50 W                                    |
| Colour of light                                      | White                                   |
| Colour temperature                                   | 3000 - 3000 K                           |
| Colour rendering index CRI                           | 80-89                                   |
| Rated luminous flux according to IEC 62722-2- 1      | 5000 - 5000 lm                          |
| Luminaire efficacy                                   | 100 - 100 lm/W                          |
| Length                                               | 175 mm                                  |
| Width                                                | 146 mm                                  |
| Height/depth                                         | 33 mm                                   |
| Filament test according to IEC 60695-2-11            | 960 °C - 30 s                           |
| Photobiological safety according to EN 62471         | RG0                                     |

---

Modern and elegant design suitable for civil, commercial and  
industri

---

|                |               |
|----------------|---------------|
| Brand          | BEGHELLI      |
| Art. N°        | B86159        |
| Sales unit     | pc            |
| EAN PCE        | 8002219758965 |
| EAN QTY PCE    | 1             |
| EAN QTY C01    | 6             |
| Intrastat code | 94054910      |