

Luminaires

The Floodlight Sensor is an outdoor floodlight with a die-cast alumin

B86168



FL LED 50W NERO IP65 SENS 3K

	B86168
With movement sensor	Yes
With presence detector	Yes
With light sensor	Yes
Lamp type	LED not exchangeable
With light source	Yes
Housing material	Aluminium
Housing colour	Black
Voltage type	AC
Nominal voltage	230 - 230 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Light distributor	Reflector
Beam angle	Open beam/diffuse
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	50000 h
Degree of protection (IP), front side	IP66
Impact strength	IK07
Protection class according to IEC 61140	I
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C
Max. system power	50 W
Colour of light	White
Colour temperature	3000 - 3000 K
Colour rendering index CRI	80-89
Rated luminous flux according to IEC 62722-2-1	5000 - 5000 lm
Luminaire efficacy	100 - 100 lm/W

The Floodlight Sensor is an outdoor floodlight with a die-cast alumin

	B86168
Length	175 mm
Width	146 mm
Height/depth	33 mm
Filament test according to IEC 60695-2-11	960 °C - 30 s
Photobiological safety according to EN 62471	RG0

Brand	BEGHELLI
Art. N°	B86168
Sales unit	pc
EAN PCE	8002219759054
EAN QTY PCE	1
EAN QTY C01	6
Intrastat code	94054910