

Luminaire

PRO LED 1X70 4000K

BF70LED



PRO LED 1X70 4K

	BF70LED
Lamp type	LED not exchangeable
With light source	Yes
Housing colour	Grey
Material cover	Glass transparent
Voltage type	AC
Nominal voltage	230 - 230 V
Type of control gear	LED operating device current-controlled
With control gear	Yes
Light outlet	Direct
Rated lifetime L70/B50 at 25 °C	160000 h
Degree of protection (IP), front side	IP66
Impact strength	IK09
Protection class according to IEC 61140	I
Rated ambient temperature according to IEC 62722-2-1	-20 - 40 °C
Max. system power	37 W
Colour of light	White
Colour temperature	4000 - 4000 K
Colour rendering index CRI	80-89
Rated luminous flux according to IEC 62722-2- 1	4000 - 4000 lm
Luminaire efficacy	108 - 108 lm/W
Length	190 mm
Width	173 mm
Height/depth	75.5 mm
Filament test according to IEC 60695-2-11	960 °C - 30 s
Colour consistency (McAdam ellipse)	SDCM3

PRO LED 1X70 4000K

Brand	BEGHELLI
Art. N°	BF70LED
Sales unit	pc
EAN PCE	8002219721488
EAN QTY PCE	1
Intrastat code	94051990