



Fittings / LED Panels

Arial Plus Multi Backlit LED UGR<19 1200x300 White Panel - 4000K



The Arial Plus Multi is our leading wattage switchable panel. With a high lumen output of up to 125 lumens per watt, this panel is ideal for areas that require high lux levels. The Arial Plus Multi can be installed in areas where TPa rated lighting products are essential, such as emergency exit routes including stairways and corridors.

- · High efficiency.
- TPa.
- Uniform light distribution.
- Professional LED Panel.
- 0-10V Dimming or DALI Dimming options available.
- · White finish.
- Anti-twist frame.
- Emergency panels with 5 year battery warranty available.
- CCT option available.

Technical Specification



11772

Reference

Guarantee	7 Years
EAN	5013588117720
Commodity Code	9405409990
Country of Origin	CN
UNSPSC Code	39111544







Technical Specification

Volts (V)	220/240
Watts (W)	20/26/30/36
Colour Temp (K)	4000
Dimmable?	No
Lumens (lm)	2500/3150/3550/4250
Life Hours	50000
CRI (ra)	85
Switching Cycles	25000
Frequency (Hz)	50/60
IP Rating	IP20
Dimensions	
Height (mm)	1195
	295
Width (mm)	
Depth (mm)	25
Packaging Information	
Single Carton Height (mm)	1282
Single Carton Width (mm)	325
Single Carton Depth (mm)	36
Single Carton Weight (kg)	2.4
Individual Volume	0.0149994
Inner Box Qty	1
Outer Box Qty	4
Outer Box Height (mm)	1295
Outer Box Width (mm)	340
Outer Box Depth (mm)	250
Outer Box Weight (kg)	14.5

